SPEC	IFICATION CO	ONTRO	_ DRAW	ING		55/033A
TITLE				Date	03-10-04	Revision C
UNSHIELDED, UNJACKETED, OUTER SPACE 03-10-04 C This specification sheet forms a part of the latest issue of Raychem Specification 55/.						
	COMPONENT WIRES - 55/03					
CABLE CONSTRUCTION DETAILS						
	PARTNUMBER <u>1</u> /	CONDUCTOR SIZE (AWG) NOMINAL MAXIMUM		hes)	MAXIMUM WEIGHT (lbs/1000 ft.)	
	55/033A-30-*	30	.044	.046	1.59	
	55/033A-28-* 55/033A-26-*	28 26	.050 .060	.052 .062	2.29 3.69	_
TEMPERATURE RATING: 150°C PARTNUMBER: Maximum continuous conductor temperature The "*" in the part numbers above shall be replaced VOLTAGE RATING: 600 volts (rms) at sea level by a color code designator with a slash separating INSULATION FLAWS: the component wire colors. Colors shown do not Spark Test, 1.5 kV (rms) necessarily reflect the sequence of manufacturing. Impulse Dielectric Test, 6.0 kV (peak) 1/ Example: AWG 30,black, brown and red component wires:						
NOTE: Nominal values are for information only. Nominal values are not requirements. Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.						
/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902" MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.						
	DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL.				tuco	Raychem Wire & Cable 01 Oakside Avenue
Page 1 of 1 THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.						Redwood City, CA 94063-3800 Phone: 1-800-227-8816 ax: 1-650-361-6297